

# RF LLF 1/2" SHF2

## Feeder cable

50Ω

SHF2

DNV


## Application

Low loss feeder cable. designed for broadband transmission from sources like radio antennas, radars, GPS devices, mobile phone antennas to distribution systems inside ships, tunnels, buildings and underground areas where RF signals normally cannot be received. SHF2 Jacket.



## Construction

Conductor	Copper coated Al wire 4.80 ± 0.05 [mm]
Dielectricum	Cellular PE 12.1 ± 0.3 [mm]
Screen	Corrugated Cu-tube 13.90 ± 0.25 [mm]
Jacket	Black SHF2
O.D.	17.0 ± 0.2 [mm]
Weight	265 [kg/km]
Jacket marking	NEK Kabel – RF LLF 1/2" – SHF2 – DNV – DD/MM/YYYY – <batch no.> – ****m



## Specifications

Operating temperature normal	-40 – +70 [°C]
Inductance	0.19 [μH/m]
Screen resistance	< 2.85 [Ω/km]
Peak RF voltage	1.8 [kV]
Characteristic impedance	50 ± 2 [Ω]
Peak power rating	32 [kW]
Conductor resistance	< 1.6 [Ω/km]
Insulation resistance	10 [GΩ x km]
Tensile strength	1100 [N]
Capacitance	76 [pF/m]
Velocity factor	0,88
Min. bending radius	60 [mm]

## Norms

Halogenfree, max content corrosive and toxic gases	IEC 60754-1 & IEC 60754-2
Material properties, insulation and sheath	IEC 60092-360 (359)
Design and testing standards	IEC 60096-0-1 Ed 3 IEC 61196-1-100
Flame resistance	IEC 60332-3-22 Cat.A
Flame retardant	IEC 60332-1
Weather resistant	ASTM G 154
Smoke emission	IEC 61034-1 & IEC 61034-2
UV-resistant	ASTM G 154 ASTM D 4587
Certification	DNV



Prod.no 3031001

## Attenuation and Power rating

Frequency [MHz]	Nominal attenuation [dB/100m] max. 105%	Power rating [kW]
30	1.66	6.9
50	2.01	5.3
88	2.51	4.0
100	2.65	3.7
200	3.58	2.6
300	4.10	2.1
400	4.31	1.8
450	4.93	1.7
500	5.20	1.6
700	5.92	1.3
800	6.37	1.3
900	6.79	1.25
1000	6.86	1.1
1400	9.14	0.9
1800	9.94	0.78
2000	10.50	0.76
2400	11.67	0.66
3000	12.90	0.58
3400	14.24	0.54
6000	21.5	0.39
8000	27.0	0.31



## VSWR

Frequency [MHz]	-
790 – 960	1.14
1700 – 1900	1.09
1920 – 2025	1.12
2110 – 2200	1.12
2300 – 2400	1.13
2515 – 2675	1.13
3300 – 3700	1.14

## Updated

Date	Rev.	Description
07.07.2023	1	Additional info + VSWR